

Date Revised: 01/30/2024

SECTION 1: PRODUCT IDENTIFICATION

Manufacturer Name	DSC PRODUCTS INC	24 Hour Emergency Telephone	(231) 739-2068
Address	1979 Latimer Dr. Building B		
	Muskegon, MI 49442		
	(517) 545-8187	www.dscprod.com	
Trade Name	MERIT	Product Type	Liquid Detergent
Chemical Family	Alcohol Sulfate	Formula	N/A

SECTION 2: HAZARDOUS IDENTIFICATION

GHS Classification: Health, acute toxicity, 5 Oral

Health, Skin corrosion/irritation, 3

Health, Serious Eye Damage/Eye Irritation, 2 B

GHS Phrases: Warning, H303 – May be harmful if swallowed

Warning, H316 – Causes mild skin irritation Warning, H320 – Causes eye irritation

GHS Label Elements:

Signal Word: Warning GHS Pictograms: None

Precautionary Statements:

Prevention: Wash hands and any exposed skin thoroughly after handling.

Wear eye/face protection. Wear protective gloves.

Response:

-Eyes IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a Poison Center or doctor/physician if you feel unwell. If eye irritation persists: Get medical advice/attention.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Name/Common Name	% (optional)	Cas.No.	OSHA PEL	ACGIH TLV (source)
2-Butoxy Ethanol	_	111-76-2	50ppm	20ppm

SECTION 4: FIRST AID MEASURES

Eyes	Flush with water, if irritation persists, consult physician			
Skin	Wash with soap and water, if irritation persists, consult physician			
Ingestion	Give large quantity of water, induce vomiting, get medical attention			
Inhalation	Remove to fresh air, if breathing is difficult, consult physician			



SECTION 5: FIRE FIGHTING MEASURES

Flash Point (T.C.C.)	N/A	Boiling	None to limits
Flammable Limits	N/A	Upper	Lower
Extinguishing Media	Water, dry chemical, foam	Special Fire Fighting	None
		Procedures	
Unusual Fire and Explosion Hazards	None		

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken if released or spilled	Dilute with water		
Waste disposal methods	Dispose to drain according to local, state and federal regulations		

SECTION 7: HANDLING AND STORAGE

Precautions to be taken in handling and storage
Other: KEEP OUT OF REACH OF CHILDREN
Keep container tightly closed and store in a cool place. Do not mix with other chemicals

SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION

Respiratory Protection		Not required unless product is atomized		
Ventilation Local X		Mechanical	Other	
Protective Gloves	Non-absorbent X	Eye Protection Glasses with sid		
Other Protective Clothing or Equipment Protect parts of body that may come in contact		ne in contact with product		
Work/Hygienic Practices		Wash with soap and water after contact		

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm – 240 mg/m3

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (degrees F)	212 F	Specific Gravity (H2O=1.0)	1.06	рН		8.0
Vapor Pressure (mm Hg)	N/A	Vapor Density (Air = 1)	N/A		ing Point rees F)	N/A
Solubility in Water	Complete X	Invisible	Emulsible (or dispersible	;)	Slight (or	partial)
Evaporation Rate (vs. H2O)		Faster	Slower About the sar		same X	
Appearance and Odor			Clear liquid			

SECTION 10: STABILITY AND REACTIVITY

Stability	Stable	Incompatibility	Strong oxidizing
			agents
Hazardous Decomposition Products	None	Hazardous Polymerization	Will not occur



SECTION 11: TOXICOLOGY INFORMATION

Threshold Limit Value – Product		None Established X		Not Applicable			
(Section 2-TLV)							
Primary Routes of Exposure		Eye X	Skin X	Oral		Inhalation	Other
Signs and Sy	mptoms of Over-expos	sure (acute)					
Eyes	Eyes Causes irritation		Skin Prolonged contact will cause absorbed readily		use irritation,		
Inhalation	nhalation May cause irritation of the respiratory tract		Ingestion		Mild toxicity may irritate gastro intestinal tract.		
Signs and Symptoms of Over-exposure (chronic)			May cause liver problems				
Medical Conditions aggravated by Over-exposure			None known				
Carcinogen or Suspect Carcinogen Ingredients			NP	ARC OSHA N		None X	

Toxicity Data:

Ethylene glycol butyl ether 111-76-2 Oral (LD 50): 917 mg/kg – Rat

Inhalation (LC 50): 2900 mg/m3/7H - Rat

Skin irritation: Mild Eye irritation: Mild

Sensitation: Not considered an occupational sensitizer

SECTION 12: ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are as followed.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT Class: Not regulated #

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

SECTION 15: REGULATORY INFORMATION

Component / (CAS/Percent) / Codes

Ethylene glycol monobutyl ether (111762 < 24%) HAP, MASS, OSHAWAC, PA, TXAIR, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

HAP = Hazardous Air Pollutants
MASS= MA Massachusetts Hazardous Substances List
OSHAWAC= OSHA Workplace Air Contaminants
PA=PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level
WHMIS = Workforce Hazardous Material Information System

www.dscprod.com



SECTION 16: OTHER INFORMATION

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact.

	Health	Fire	Reactivity	Special	Personal Protection Index
NFPA	1	1	0	0	В
HMIS	1	1	0	0	В

Note to Reader

The information contained herein is deemed accurate and complete at the time of this publication. Use of the product beyond care, custody and control of the manufacture shall bear no warranty whether implied or expressed. DSC Products, Inc. assumes no liability for injury to any person or property resulting of this product without strict adherence to safety procedures. User bears all risks concerning use of the product as designated through labeling. It is recommended any and all data, directives and recommendations should be followed accordingly. This does not apply to any combination with other materials, chemical compounds or processes not inclusive of aforementioned specifications.