



FIBER-TEC

DESCRIPTION:

Fiber-Tec (previously known as Fiber-Tec 1:4) is a concentrated water based carpet and upholstery protector formulated for ease of use. Fiber-Tec protects against both oil and water based stains and repels dry soil, leaving a protected surface that resists reoccurring soils and stains. With no fluorocarbons or solvents, Fiber-Tec is safe to use in all indoor environments and can be applied without fear of damage to the carpet or upholstery one is working with.

DIRECTIONS:

Dilute 1:4 (32 oz. per gallon) for use on damp carpet. Get 5 gallons of RTU protector using 1 gallon of Fiber-Tec to 4 gallons of water. For dry carpet, dilute the RTU solution 1:1 to make 2 gallons of new mixture.

Apply Fiber-Tec with a low-pressure, non-atomizing sprayer. Be sure that the fibers or fabric is saturated (damp to the touch) when applying. Fibre-Tec will dry clear and works the best after letting cure for 24 hours after drying. To test if the area is still protected, lightly mist cold water on the carpet. If the water stays on top of the fibers, then the carpet is still protected.

PACKAGING OPTIONS:

- 4/1 gal.
- 55 gal.



SPECIFICATIONS:

Appearance: White milky liquid

Odor: None

pH: 7-8

Storage: Do not freeze.

Freeze/Thaw: Does not recover after freezing.



www.dscprod.com
1979 Latimer Dr, Building B
Muskegon MI, 49442
info@dscprod.com
phone (517) 545-8187