



FIBRE-TEC OMS

DESCRIPTION:

Fibre-Tec OMS is a solvent based carpet protector that evaporates quickly and leaves behind a clear and strong fluorocarbon based protective layer on most fabrics and carpets. This fluorocarbon gives the fabric a water repellent coating that has the added benefit of avoiding stains caused by common spills and soils. Fibre-Tec OMS's low odor formula makes it easy to apply indoors, while not compromising on strength or drying times. Once the solvent is evaporated, the fluorocarbon coating is safe for handling - whether on carpet, upholstery, or fabrics.

DIRECTIONS:

Fibre-Tec OMS should not be diluted with water or solvents and should be applied as-is. For all applications: Use a box fan or some form of air circulation and open windows or doors if possible to generate air circulation. Ventilation is necessary for safety and fast drying times.

On dry carpet/fabric: Only apply to dry carpet that has been cleaned and rinsed first. Improper cleaning will affect protective coating. Apply with non-atomizing sprayer and apply no more than one gallon per 600 sq. ft. With proper ventilation, carpet should be dry after an hour, and cured after 12.

On wet carpet/fabric: Let carpet or upholstery dry until it is only damp to the touch. If the surface is too wet, Fibre-Tec OMS will not work. Once carpet or upholstery is no more than damp, spray over a small area and check that the product is coating the fibers. Once it is confirmed that fibers are coated, apply a full treatment of Fibre-Tec OMS.

PACKAGING OPTIONS:

- 4/1 gal.



SPECIFICATIONS:

Appearance: Clear colorless liquid

Odor: Faint petroleum

pH: N/A

Storage: Store at room temperature away from sparks or open flame.

Freeze/Thaw: Will not freeze.



www.dscprod.com
1979 Latimer Dr, Building B
Muskegon MI, 49442
info@dscprod.com
phone (517) 545-8187